

L3 ANSWER 7 OF 10 JAFIO COPYRIGHT 1999 JPO and Japio
 AN 1991-192952 JAFIO
 TI FACSIMILE EQUIPMENT
 IN TAKAHASHI TOSHIHIKO
 PA NEC CORP, JP (CO 000423)
 PI JPO3192952 A 19910822 Heisei
 AI JPI989-333503 (JPO1333503 Heisei) 19891222
 SO PATENT ABSTRACTS OF JAPAN, Unexamined Applications, Section: E, Sect. No.
 1135, Vol. 15, No. 454, P. 6 (19911119)
 IC ICM (5) H04M011-00
 ICS (5) H04N001-32
 CC 44.4 COMMUNICATION - Telephone
 44.7 COMMUNICATION - Facsimile
 AB PURPOSE: To recognize the state at the end of communication even when the
 operator **leaves** the equipment after the operation of the
 transmission by calling a telephone set entirely independent of the
facsimile equipment and **informing** the content of a
fault in a voice from a voice synthesis section in the occurrence
 of a communication **fault**.
 CONSTITUTION: When an equipment control section 3 decides it that a
 communication end state signal is a signal representing a communication
fault, the section 2 outputs a **fault** notice request
 signal 34 to a **fault** notice section 4 and the **fault**
 notice section 4 outputs a voice synthesized request signal 45 to a voice
 synthesis section 5. Moreover, the **fault** notice section 4
 outputs a readout request signal 41 of a telephone set 10 to a network
 control section 1 and makes dialing. When the telephone set 10 is called
 and a reply signal is detected, the **fault** notice voice signal 51
 synthesized by the voice synthesis section 5 is **informed** to the
 telephone set 10 via the network control section 1. Thus, even when the
 operator **leaves** the **facsimile** equipment 2 after the
 operator makes transmission from the **facsimile** equipment 2 to
 the **facsimile** equipment 1, the occurrence of communication
fault is recognized.